



EX-SDI(HD-SDI) 발열감지 카메라

Thermal-T36.5-Coax



| | | |
|--------------------------|---------------------|--|
| Sensor Type | | 1/2.8", 2.1Megapixel Sony STARVIS Sensor |
| Total Pixels | | 1920 (H) × 1080 (V) = 2.1M pixels |
| Scanning System | | Progressive Scan |
| Thermal | Sensor | LWIR Sensor, wavelength 8~14 um |
| | FOV / Distance | 51° (HFOV), 39° (VFOV) / 1~5m, More than 6m |
| | Detection Degree | 30°C ~ 40°C |
| | Emissivity | MATT(0.96), SEMI_MATT(0.80) SEMI_GLY(0.60), GLOSSY(0.3), MANUAL(0.1 ~ 0.99) |
| | Minimum Object Size | Distance 1m : 0.05m (H) x 0.05m (V) Distance 10m : 0.5m (H) x 0.5m (V) |
| | Detection Time | 1, 3, 5, 10 sec. |
| | Action Time | Keep On, 1, 3, 5, 10, 20, 30, 40, 50, 60 sec |
| | Alarm Output | OFF / ON (Active Low, Active High) |
| Lens | Filter | True Day & Night (ICR) |
| | Type | 3.6mm FIXED MEGA LENS (ICR) |
| Video | Output | 1 (BNC 1.0 Vp-p, 75Ω) |
| | Resolution | 1080p 30fps / 25fps |
| | Format | HD-SDI / EX-SDI / EX-SDI 2.0 |
| Video Control | AGC | LEVEL 0~10 |
| | S/N Ratio | More than 52dB |
| | BLC | OFF / HLC / BLC / WDR |
| | ACE | OFF / LOW / MIDDLE / HIGH |
| | Min. Illumination | 0.02Lux (DSS X32) |
| | DNR | OFF / LOW / MIDDLE / HIGH |
| | Iris Adjust. | MANUAL |
| | White Balance | AUTO / AUTOext / PRESET / MANUAL |
| | Electric Shutter | INDOOR / OUTDOOR / INDOOR-ANTI-BLUR / OUTDOOR-ANTI-BLUR / FLICKER / MANUAL (11 Steps) |
| | OSD Language | ENG |
| | Day&Night | COLOR / BW / EXTERN / AUTO |
| | Defog | OFF / ON (AUTO, MANUAL-LOW / MIDDLE / HIGH) |
| | Privacy | Not Supported |
| | Face Recognition | MAX 10 users |
| | Defect | LIVE DPC |
| | DSS | OFF / X2~X32 |
| | Digital Effect | OFF / H-MIRROR / V-MIRROR |
| | IR LED | 30 pcs |
| | Smart IR | OFF / ON |
| Input Voltage | | DC 12V(±10%, Adapter) |
| Power Consumption | | IR OFF : 3W (MAX) IR ON : 5W (MAX) |
| Operation Temp./Humidity | | -10°C ~ +50°C / MAX 90% RH |
| Storage Temp./Humidity | | -20°C ~ +60°C / MAX 90% RH |
| Certification | | KC |